



ER2500T Articulating Compact Loader Spec Sheet



Standard Features	Telescopic Loader Arm
	Standard Bucket w/ Removable teeth
	Rops & Fops Premium Cabin
	Luxury Interior
	Quick Hitch
	Electric Joystick
	Extra Hydraulic Line
	Comfort Seat
	Adjustable Steering
	130w Heater
	Block Heater
	Reverse Camera
	Air-Brake System
Blinking Lamp	

Upgraded Features & Extras	Upgraded 5 button joystick with quick detach
	A/C
	Loader Dampener
	Bobcat/skidsteer Style Quick Detach System
	8 Gears Shift
	Upgraded Air-ride seat w/ pump
	LED Work Lights
	16/70-20 Snow Tire Upgrade
	Hydraulic Float Function
	Hand Throttle
	Diesel Cabin Heater
	Sound Insulated Cabin

Engine	Model	Cummins QSF2.8 EPA4
	Horsepower	55KW (74hp)
	Engine Cooling System	Water Cooled

	Type	Inline 4cyl Diesel (non-def)
Bucket	Bucket Capacity	0.67m3 (23.66ft3)
	Bucket Width	2018mm (79.44in)
	Type	Heavy Duty w/ Removable Teeth
Overall Dimensions	Length	5755mm (226.5in)
	Height	2740mm (107.9in)
	Width	1870mm (73.6in)



Brake System	Service Brake	Air-assisted hydraulic brake
	Park Brake	Hand operated (manual disc)
	Braking Type	Air Braking

Max Lift Height	4500mm (177in)
Max Dump Height	3848mm (151.5in)
Max Dump Reach	1124mm (44.2in)
Rated Load	2500kg (5511lb)
Transmission System	Hydraulic converter + drive shaft + Axles
Wheelbase	2430mm (95.6in)
Min Turning Radius (outside of wheels)	4613mm
Oscillation angle	8 Degrees
Track Width (wheelstance)	1470mm (57.9in)
Overall Weight	5300kg (11,684lb)
System Pressure	20Mpa (2900psi)
Hydraulic Output:	96L/min
Max Height to Pin	4200mm (165.3in)
Max Tractive Force	35kN (7868lb-force)
Max Breakout Force	25kN (5620lb-force)
Max Grade Ability	20 Degrees

